

Voice Fiber Mux Series (FXO/FXS/POTS/E1)



ORDERING INFORMATION

TELESCIENCE (SINGAPORE) PTE LTD
61 Kaki Bukit Avenue 1, #04-08, Shun Li
Industrial Park, Singapore 417943
Tel: 6749 7878 Fax: 6749 4700
Email: sales.sg@telescience.asia

SPOTLIGHT

AN-FM-PCM30 fiber mux is an optical transmission equipment realizing long-distance voice transmission through fiber. Primary interfaces are FXS/FXO but additional E1, Ethernet or E1 can be added upon request

DESCRIPTION

This equipment uses design of ultra large scale integrated circuit, and its outward appearance is succinct. The merits include easy installation and debugging, unnecessary for maintenance and steady performance. It is suitable in business for communication operator, government and kinds of entities.

AN-FM-PCM30 fiber mux can provide 1-8 channels, 1-16 channels, 1-24 channels, or 1-30 channels telephone through optical cable, the network application is point-to-point, supporting FXO/FXS. It has solved telephone transmission problem of edge customers. This equipment uses special digital multiple-connected chip whose function is formidable, and it integrates nearly all the digital logical function of equipment, thus remarkably enhancing product performance and reducing cost. Additional channels of E1, Ethernet and RS-232 can be added upon request.

FEATURE

- Low cost solution for delivering analogue POTS lines over long distance fibers;
- up to 30 FXO ports for connection to PABX or PSTN;
- up to 30 FXS ports for connection of phones or faxes;
- Ethernet port for LAN interconnection;
- RS-232 for data transmission
- Up to 4E1 ports as an option for PABX interconnection or any other E1 Leased lines services
- MTBF more than 10 years
- WDM Bidi fiber interfaces available

SPECIFICATION

FXS ringing voltage: 75V ringing frequency: 25HZ	Optical Interface Parameter optical wavelength: 850nm/1310nm for multi-mode optical interface, 1310nm/1550nm for single-mode optical interface optical interface: SC/FC receiving and dispatching module: >-6dBm optical receiver receiving sensitivity <-36 (BER<10): dynamic receiving range: >-30dB transmitting range: Multi-mode 2 Km, single-mode 40Km, single-mode 60 Km, single-mode 120Km, WDM bidi available vibration characteristic: Comforms G.742 and G.832 standard
FXO two line input impedance: 600 Omega (hanging off) wastage: 40 db ringing detecting voltage: 35V	

Application example:

